

# LINEAR



# Ac0207



MOTOR FREE  
PISTON SYSTEM



## Airflow & Power Consumption




## Specifications


	(SI)	(EURO)	(U.S.A.)
Rated Pressure	0.07 MPa {0.7 kgf/cm <sup>2</sup> }	0.7 bar	9.96 psig
Rated Airflow	3.5 l /min		
Rated Voltage	115 V, AC or 230 V, AC		
Maximum Pressure	0.1 MPa {1.0 kgf/cm <sup>2</sup> }	1.0 bar	14.2 psig
Power Consumption	20 W or 25 W		
Rated Frequency	60 Hz or 50 Hz		
Life Expectancy	3,000 hours		
Outlet	4.7 mm O.D. hose nipple		
Duty Cycle	Continuous		
Coil Insulation Class	E or its equivalent (JETL) or B for UL		
Mounting Dimensions	75 (L) x 88 (W) mm		
Gross Weight	1.7 kg		3.7 Lbs.
Leadwire Length	200 mm		7-7/8"

\* Life expectancy is the expected accumulated period of time during which the compressor will maintain the above specifications. Contact your supplier for details of the conditions of use under which the values and numbers stated herein are maintained.

## Application Examples






Air Bearing for Precision Machines



Nebulizer

## Sketch Drawing and Mounting Dimensions Diagram (mm)



View A